


TOILON THERMOTEC[®]

Thermal CrossLinked Closed Cell FR CLASS O



XLPE
CHEMICALLY CROSSLINKED
CLOSED CELL FOAM FR CLASS O

CROSS-LINKED FOAM
HVAC & DUCT INSULATION
ROOF & CLADDING INSULATION



SAVE ENERGY & COOLING COST



thermo.co.id
thermotech indonesia

SAVE
ENERGY & COOLING COST
With CrossLinked Foam



CLOSED CELL FOAM FR CLASS O

Building & Constructions Safety Regulation & Standard International (Certification and Testing Report)

Toilon Thermotech® is crosslinked foam technology manufactured, which is polyolefin material is very suitable for insulation used in HVAC & Duct, Roof, Wall, Cladding, Pipe, Raised Floor & Underlayer which provides excellent performance.

Toilon Thermotech® products are guaranteed up to 20 Years certified warranty so that Toilon Thermotech® products are extremely durable and long lasting. Our commitment to maintaining quality and it is proven by conducting ISO 9001.

Toilon Thermotech® product certified with FR Rating Class O (EXOVA & TUV), and ASTM E84-24 with Flame Spread index = 5 & Smoked Development Index = 20 with Compliance of Certificate from UL94, etc. All Certificate recommended for safety building materials.

Toilon Thermotech® crosslinked foam closed cell technology is a product with high innovation with two type Crosslinked Product :

- a. IXPE - Physically Crosslinked Foam Closed Cell** , produces with electron beam machine for Crosslinking Polymer Progress.
- b. XLPE - Chemically Crosslinked Foam Closed Cell** , with chemically mixing machine for crosslinking polymer progress.

Proven Reliability & Experience Since 2001 (special quality material control)

Toilon Thermotech® thermal insulation technology has been experienced in foam insulation field since 2001. Toilon Thermotech® is The FIRST & BIGGEST CrossLinked Technology with experience more than 20 years and leading number 1 in local market Indonesia.

Therefore, we are here in Indonesia to meet all your insulation needs such as: HVAC, roof, walling, pipe, raised floor, underlay and building insulation, etc. Which provides excellent performance and best quality of production.

Technically Superior

Our distinctive CrossLinked technology produces a smaller and more evenly fine cell structure. Thermal conductivity and vapour permeability, which are the key factors in insulation performance, are directly affected by the cell structure.


Thermal Conductivity (ASTM C-518)

0.0316 W/m.K

0.0272 (Kcal/mhK)

Mean Temp : 23°C

It is the lowest amount of any flexible insulation material.



Chemically Crosslinked Technology

XLPE Chemically Crosslinked Technology :


- Strong & Great Surface with Fine Closed Cell
- High Vapour Permeability Resistance



Foam Oven Expanding Machine
(XLPE-Chemically CrossLinking
polymer Process)

Almost Zero Vapour Permeability

Permeability This property guarantees that the thermal conductivity stays relatively constant for up to 15 years which will give a significant contribution to building sustainability and lowering energy cost.



Third Party Certification & Testing

To maintain the quality of products that are produced in house from our factory, we carry out certification testing periodically through a credible and internationally recognized institution :

- ✔ American Standard Testing and Material (ASTM) - USA
- ✔ British Standards (BS) - United Kingdom
- ✔ EXOVA Warrington Fire Tested - United Kingdom
- ✔ Intertek Testing Services - United Kingdom
- ✔ Australian Wool Testing Authority - Australia
- ✔ Underwriters Laboratories - USA (UL 94)
- ✔ Technischer Überwachungs Verein - Germany (TUV - PSB Singapore)
- ✔ Societe Generale de Surveillance - Switzerland (SGS - Korea)
- ✔ Korea Laboratory Accreditation Scheme (KOLAS) - Korea
- ✔ International Laboratory Accreditation Cooperation (ILAC - MRA)
- ✔ Tingkat Komponen Dalam Negeri (TKDN) - Indonesia
- ✔ Kementerian Perindustrian - Indonesia
- ✔ International Organization for Standardization (ISO) - United Kingdom
- ✔ MSA Certification - SNI ISO 9001:2015 - Indonesia
- ✔ MSA Certification - SNI ISO 14001:2015 - Indonesia


International Fire & Smoke Standards for Building Insulation (Duct/Raised Floor/Roof/Cladding)

- ✔ British Standards BS 476 (Parts 6 & 7)
- ✔ American Standards ASTM E84
- ✔ AWTA Product Testing Method : AS/NZS 1530.3-1999
- ✔ Underwriters Laboratories - USA (UL 94)

Quality Materials

To maintain the stability of the quality of our products, we conduct routine Product Testing compiled with *Underwriters Laboratories - USA (UL 94)* for raw material and product line audits every 3 months.





Product Application




✓ HVAC & Duct Insulation

Insulation from crosslinked Polyolefin foam. It has low thermal conductivity and a closed cell structure and is reinforced with a layer of lamination on the outer surface.




✓ Underlayer Insulation

Placing acoustic or insulation underlay underneath your flooring greatly enhances your living comfort, as it noticeably reduces reflected walking noise.




✓ Roof Insulation

The use of roof insulation Heat Absorbers can reduce energy loss. Maintaining Consistent Stable Room Temperature.



✓ Raised Floor Insulation

Raised Floor is a model and construction method in data center buildings by creating additional floors with a height of several centimeters from the concrete floor or main floor of a building.



✓ Pipe Insulation (ThermoTube)



Insulation has excellent durability & flexibility power. It is used in flexible temperature between -80°C ~ 100°C .



✓ Cladding Insulation

Cladding is the outer layer that protects the core and reflects the light that radiates out back into the core.

ROOF & CLADDING INSULATION



HVAC & DUCT INSULATION




Type of CrossLinked XLPE Foam

- ✓ Chemically CrossLinked Technology
- ✓ Thermal Foam Insulation
- ✓ The highest Fire Rating Class 0
- ✓ Strong & Great Surface with Fine Closed Cell
- ✓ High Vapour Permeability Resistance
- ✓ Water Resistance Protect
- ✓ Lifetime More Than 15 Years** (T&C Applied)



A. Premium Protection for Indoor & Outdoor (Premium UV)

- ✓ Total Alum Thickness Material : 70 ~ 80 micron
- ✓ Radiant Reflectivity up to 95.7 %
- ✓ Emissivity : 0.13 (Low Re-radiation)
- ✓ Strong with Anti Tear Aluminum
- ✓ Anti Corrosion & Anti UV Protection Aluminum



B. General Protection for Indoor (Eco)

- ✓ Total Alum Thickness Material : 50 ~ 60 micron
- ✓ Radiant Reflectivity up to 85 %
- ✓ Emissivity : 0.06 (Low Re-radiation)
- ✓ Strong with Anti Tear Aluminum

Product Accessories

• THERMAL FOAM TAPE



Type Product :

- > Foam Only With Glue (F0G)
- > Alum Foil With Glue (AF1G)

Size Availability :

- > 5 mm x 1 inch x 10 mtr
- > 5 mm x 2 inch x 10 mtr


• ALUMINUM TAPE (DUCT TAPE)



Size Availability :

- > 48 mm x 30 mtr (2 Inch)
- > 72 mm x 30 mtr (3 Inch)

• METALIZE TAPE



Size Availability :

- > 48 mm x 30 mtr (2 Inch)

• PLATSTREEP ZINCALUME



Size Availability :

- > 30 mtr x 5 cm (0,3 mm TCT)
- > 30 mtr x 8 cm (0,3 mm TCT)

• GLUE BLACK PREMIUM



Type Product :

- Glue Black Premium 220
- Size Availability : Uk.10kg / Blek

ThermoTech Support Technology is a simple and accurate software tool for calculating insulation thickness using Overall Thermal Transfer Value (OTTV) and Roof Thermal Transfer Value (RTTV) calculations for green building standards.

Thermo calculator provides solutions with accurate calculations, which can provide the following benefits :

✓ Save Energy Costs

- With proper insulation, heat is not easily lost or absorbed, thus reducing electricity or fuel consumption for heating/cooling.
- Reduces over insulation (insulation that is too thick wasted material costs) and under insulation (insulation that is too thin wasted energy).

✓ Reduced Maintenance Costs

- Avoids condensation on surfaces, which can cause corrosion.
- Reduces equipment wear and tear due to temperature fluctuations.
- Reduces the risk of fire or thermal leakage.

✓ Standards Compliance

- Many industry standards (e.g., SNI, ISO, ASHRAE, Green Building) require certain levels of insulation for energy efficiency. The Thermo Calculator helps ensure designs comply with these standards.



ThermoTech Support Technology

www.thermocalculator.co.id



Project Reference





GEDUNG GWW IPB



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



INDOFOOD PONTIANAK



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



WAREHOUSE SPIL CIBITUNG



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



WAREHOUSE BEKA SUBANG



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



JAINDO PDIP PURWAKARTA



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



GEDUNG PERTEMUAN SLEMAN



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



BIZPARK - PIK 2



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



SHINWON FACTORY



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION



PT. ULTRA SAKTI



ROOFING INSULATION



ROOFING INSULATION



ROOFING INSULATION





BETA PHARMACON



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



DAEWONG SELATOX



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



RS EDELWEISS



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



DAIKIN FACTORY



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



RS TRIA DIPa



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



NESTLE



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



PABRIK CERES BANDUNG



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



KINO SAYUNG DEMAK



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



UNILEVER SKIN ZARA



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION



HVAC & DUCT INSULATION





GOLDEN SENSE INTERNATIONAL RESTAURANT



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



SWISSOTEL IKN



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



MESJID SYEIKH ZAYED



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



HOTEL LAXSTON



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



HOTEL MERCURE TANGERANG CENTRE



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



MERCURE HOTEL



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



OAKWOOD



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



JAKARTA AIRPORT HOTEL



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION



GSG UNIVERSITAS DIPONEGORO



UNDERLAYER INSULATION



UNDERLAYER INSULATION



UNDERLAYER INSULATION

