

Plastics - Component

COMPANY

PT TOILON INDONESIA
 JL. RAYA SERANG KM 16. 8
 DESA TELAGA CIKUPA
 TANGERANG, Banten 15710 Indonesia

E356051

Dsg	Color	Min Thk mm	Flame Class	H		Elec Str	RTI		H	D	C
				W	A		Mech	Str	V	4	
Polyethylene (PE) furnished as Sheets and Rolls											
25(a)	WT	7.0	HF-1	-	-	50	50	50	-	-	-
		13.0	HF-1	-	-	50	50	50	-	-	-

(a) - Denotes 2 digit numbers for thickness.

Marking: Company name or trademark  , **TOILON** ,  , material designation On container, wrapper Or finished part.

Last Updated on 2022-02-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Feedback

Model 25(a)

File Number: E356051

Yellow Card® 

COMPANY

PT TOILON INDONESIA
 JL. RAYA SERANG KM 16. 8
 DESA TELAGA CIKUPA
 TANGERANG, Banten 15710 Indonesia

MODEL INFO

25(a)

Polyethylene (PE), furnished as Sheets and Rolls

(a) – Denotes 2 digit numbers for thickness.

This product has not been received for testing as part of UL Follow-Up Services in the past four years and cannot currently be distributed as a UL Certified product.

[Click here to learn more.](#)

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
7.0 mm, Color: WT	HF-1	
13.0 mm, Color: WT	HF-1	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ISO 9772
7.0 mm, Color: WT	HF-1	
13.0 mm, Color: WT	HF-1	
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
7.0 mm	50 °C	
13.0 mm	50 °C	

Relative Thermal Index - Mechanical Impact		UL 746B
7.0 mm	50 °C	
13.0 mm	50 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
7.0 mm	50 °C	
13.0 mm	50 °C	

Report Date: 2012-07-27
Revision Date: 2022-02-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."